The new degree of comfort.™

Professional *Classic Plus*™ Power Vent gas water heaters offer up to 100 foot vent runs, energy efficiency and the Guardian System

Efficiency

- .67 EF
- ENERGY STAR® rated

Performance

- FHR: 85 gallons for 50-gallon model and 71 gallons for 40-gallon model
- Recovery rate is 36.4 for 50-gallon model and 32.4 for 40-gallon model at a 90 degree rise

Self-Diagnostic System

 Electronic gas control for improved monitoring and service



Low Emissions

• Eco-friendly burner, low NOx design

Features

- Uses indoor air for combustion; blower exhausts the flue gases
- Standard 120 VAC electrical connection
- New whisper quiet blower

Guardian System[™] & Sensor

- Exclusive air/fuel shut-off device
- Maintenance free no filter to clean
- Disables the heater in the presence of flammable vapor accumulation





ombustion Shut-off System

Flame Arrestor Plate



Flexible Venting Options

• Long venting lengths up to 100

- Long venting lengths up to 100 equivalent feet
- PVC or CPVC certified to ULC-S636 vent pipe options
- Vertical or horizontal termination

Longer Life

 Rheem exclusive R-Tech (resistored) anode rod provides long-lasting tank protection

High Altitude Compliant

 Certified for applications up to 6,000 feet above sea level

Plus...

- Enhanced flow brass drain valve
- Temperature and pressure relief valve included
- Low lead compliant
- Durable Silicon Nitride Ignitor (HSI)
- EverKleen[™] patented system fights sediment build-up
- Standard replacement parts

Warranty

- 8-Year limited tank and parts warranty*
- With ProtectionPlus™ the 8-year limited tank warranty becomes 10-year ProtectionPlus – order part number SP20081 (6 pack only)

*See Residential Warranty Certificate for complete information



Professional Classic Plus Power Vent

40 and 50-Gallon Capacities Up to 36,000 Btu/h Natural and LP Gas










LLLD I OIIK - I

See dimensions chart on back.

Professional Classic Plus™ Power Vent Specifications

		DESCRIPTION	FEATURES				ROUGHING IN DIMENSIONS (SHOWN IN INCHES)					ENERGY INFO.					
T Y P	GAL.	MODEL	GAS IN		RECOV G.P.H. 9		FIRST HOUR DEL. G.P.H.	HT. TO TOP OF ASSEMBLY	TANK HT.	DIAM.	HT. TO GAS CONN.	WATER CONN. CNTR.	HT. TO SIDE T&P VALVE	WATER CONN. SIZE	SHIP. WT.	ENERGY FACTOR	AVG. ANNUAL OPER. COST
	CAP.	NUMBER	NAT.	LP	NAT.	LP	NAT.	A	В	C	D	E	F	G	(LBS)	NAT.	NAT.
Short	40	PRO+G40S-36N CN67 PV	36	32	36.4	32.4	71	62-1/2	51-1/4	21-3/4	14	8	44-1/4	3/4	155	0.67	\$272
Short	50	PRO+G50S-36N CN67 PV	36	32	36.4	32.4	85	62-1/2	51-1/4	23-3/4	14	8	44	3/4	175	0.67	\$272

Specify LP when ordering. Add gas input and "P' to the model number. Example: PRO+G40S-32P CN67 PV



Maximum and Minimum Vent Lengths for 2" Vents

NUMBER OF 90° ELBOWS WITH VENT TERMINAL	NUMBER OF 45° ELBOWS	MINIMUM PIPE LENGTH REQ. (FT.)	MAXIMUM PIPE LENGTH (FT.) 0' - 2000'	MAXIMUM PIPE LENGTH (FT.) 2000' - 7700' *
One (1)	None	4.0	44.0	24.0
One (1)	One (1)	4.0	41.0	21.0
Two (2)	None	4.0	38.0	18.0
Two (2)	One (1)	4.0	35.0	15.0
Three (3)	None	4.0	32.0	12.0

For the 2" vent, one 90° elbow is approximately equal to 6 feet of pipe. One 45° elbow is approximately equal to 3 feet of pipe. *2,000' - 6,000' for short models.

Maximum and Minimum Vent Lengths for 3" Vents

NUMBER OF 90° ELBOWS WITH VENT TERMINAL	NUMBER OF 45° ELBOWS	MINIMUM PIPE LENGTH REQ. (FT.)	MAXIMUM PIPE LENGTH (FT.) 0' - 2000'	MAXIMUM PIPE LENGTH (FT.) 2000' - 7700' *		
One (1)	None	5.0	95.0	75.0		
One (1)	One (1)	5.0	92.5	72.5		
Two (2)	None	5.0	90.0	70.0		
Two (2)	One (1)	5.0	87.5	67.5		
Three (3)	None	5.0	85.0	65.0		

For the 3" vent, one 90° elbow is approximately equal to 5 feet of pipe. One 45° elbow is approximately equal to 2.5 feet of pipe. *2,000' - 6,000' for short models.

In keeping with its policy of continuous progress and product improvement, Rheem reserves the right to make changes without notice.